

## DECLARATION OF PERFORMANCE (ZER0.3 3Plus)

No DOP004PAN

1. Unique identification code of the product-type

**Dry-pressed ceramic tiles with low water absorption  $E_b \leq 0,5\%$ .**

2. Intended use

**Ceramic tiles for internal flooring and internal and external wall applications, pre-assembled on a fibreglass mesh.**

3. Name and contact address of the manufacturer

**PANARIA CERAMICA, via Panaria Bassa 22/a, 41034 Finale Emilia (MO) – ITALY**


4. System of assessment and verification of constancy of performance of the construction products (AVCP)

**System 4**

5. Name and identification number of notified body, if applicable

**Not applicable**

6. Declared performance


Essential characteristics	Performance	Harmonised technical specifications
Reaction to fire	A2 <sub>fl</sub> -s1/A2-s1,d0	 <p>EN 14411:2012</p>
Release of dangerous substances		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	NPD	
Modulus of rupture	$\geq 35 \text{ N/mm}^2$	
Slip resistance	See Annex enclosed	
Tactility	NPD	
Adhesion resistance		
- Cementitious adhesive C1 class	NPD	
- Cementitious adhesive C2 class	NPD	
Thermal shock resistance	Passed	
Durability		
- Internal use	Passed	
- External use: Frost resistance	Passed	

7. The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Finale Emilia, April 03, 2024

Signed for and on behalf of the manufacturer by



Marco Levoni, Panaria Ceramica Quality Dept.

## Annex to the Declaration Of Performance N. DOP004PAN

Slip resistance			
Series	Products	DIN EN 16165 Annex B	BCRA D.M. 236/1989
ZERO.3 Blade	Oxide, Chrome, Petrol, Rust, Essence	NPD	NPD
ZERO.3 Experience	Bianco Denso Plus 3,5mm, Beige Tenue Plus 3,5mm, Grigio Vivo Plus 3,5mm, Nero Puro Plus 3,5mm	R9	NPD
Zero.3 - Must	Star White Smooth	NPD	NPD
ZERO.3 Urbanature	Lime Plus 3,5 mm, Concrete Plus 3,5 mm, Cement Plus 3,5 mm, Portland Plus 3,5 mm, Silicon Plus 3,5 mm	R9	>0,40