


## DECLARATION OF PERFORMANCE (ZER0.3 3Plus)

No **DOP004PAN**

1. Unique identification code of the product-type  
**Dry-pressed ceramic tiles with low water absorption  $E_b \leq 0,5\%$ .**
2. Intended use  
**Ceramic tiles for internal flooring and internal and external wall applications, pre-assembled on a fibreglass mesh.**
3. Name and contact address of the manufacturer  
**PANARIA CERAMICA, via Panaria Bassa 22/a, 41034 Finale Emilia (MO) – ITALY**
4. System of assessment and verification of constancy of performance of the construction products (AVCP)  
**System 4**
5. Name and identification number of notified body, if applicable  
**Not applicable**

6. Declared performance

Essential characteristics	Performance	Harmonised technical specifications
<b>Reaction to fire</b>	A2 <sub>fl</sub> -s1/A2-s1,d0	
<b>Release of dangerous substances</b>		
- Cadmium	NPD	
- Lead	NPD	
<b>Breaking strength</b>	NPD	
<b>Modulus of rupture</b>	$\geq 35 \text{ N/mm}^2$	
<b>Slip resistance</b>	See Annex enclosed	
<b>Tactility</b>	NPD	
<b>Adhesion resistance</b>		
- Cementitious adhesive C1 class	NPD	
- Cementitious adhesive C2 class	NPD	
<b>Thermal shock resistance</b>	Passed	
<b>Durability</b>		
- Internal use	Passed	
- External use: Frost resistance	Passed	

7. The performance of the product identified in point 1 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Finale Emilia, March 31<sup>th</sup> 2021

Signed for and on behalf of the manufacturer by

*Enrico Mantovani*

Enrico Mantovani, Panaria Ceramica Quality Dept.

## Annex to the Declaration Of Performance N. DOP004PAN

<b>Slip resistance</b>			
<b>Series</b>	<b>Products</b>	<b>DIN 51130</b>	<b>BCRA D.M. 236/1989</b>
ZERO.3 Blade	Oxide, Chrome, Petrol, Rust, Essence	NPD	NPD
ZERO.3 Experience	Bianco Denso Plus 3,5mm, Beige Tenue Plus 3,5mm, Grigio Vivo Plus 3,5mm, Nero Puro Plus 3,5mm	R9	NPD
ZERO.3 Urbanature	Lime Plus 3,5 mm, Concrete Plus 3,5 mm, Cement Plus 3,5 mm, Portland Plus 3,5 mm, Silicon Plus 3,5 mm	R9	>0,40