

## DECLARATION OF PERFORMANCE (ZER0.3 6mm)

No DOP006PAN

1. Unique identification code of the product-type

**Dry-pressed ceramic tiles with low water absorption  $E_b \leq 0,5\%$ .**

2. Intended use

**Ceramic tiles for internal flooring and internal and external wall applications.**

3. Name and contact address of the manufacturer

**PANARIA CERAMICA, via Panaria Bassa 22/a, 41034 Finale Emilia (MO) – ITALY**


4. System of assessment and verification of constancy of performance of the construction products (AVCP)

**System 4**

5. Name and identification number of notified body, if applicable

**Not applicable**

6. Declared performance

| Essential characteristics        | Performance                 | Harmonised technical specifications   |
|----------------------------------|-----------------------------|---|
| Reaction to fire                 | A1fl/A1                     | <br><b>EN 14411:2012</b> |
| Release of dangerous substances  |                             |   |
| - Cadmium                        | NPD                         |   |
| - Lead                           | NPD                         |   |
| Breaking strength                | $\geq 700$ N                |   |
| Modulus of rupture               | $\geq 35$ N/mm <sup>2</sup> |   |
| Slip resistance                  | See Annex enclosed          |   |
| Tactility                        | NPD                         |   |
| Adhesion resistance              |                             |   |
| - Cementitious adhesive C1 class | NPD                         |   |
| - Cementitious adhesive C2 class | NPD                         |   |
| Thermal shock resistance         | Passed                      |   |
| Durability                       |                             |   |
| - Internal use                   | Passed                      |   |
| - External use: Frost resistance | Passed                      |   |

7. The performance of the product identified in point 1 is in conformity with the declared performance in point 6.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Finale Emilia, March 26<sup>th</sup> 2019

Signed for and on behalf of the manufacturer by

*Enrico Mantovani*

Enrico Mantovani, Panaria Ceramica Quality Dept.

## Annex to the Declaration Of Performance N. DOP006PAN

| Slip resistance     |   |           |                    |
|---------------------|---|-----------|--------------------|
| Series              | Products  | DIN 51130 | BCRA D.M. 236/1989 |
| ZERO.3 Context 6mm  | Square, Loft, Store, Hangar, Mansion  | R10       | >0,40              |
| ZERO.3 Eternity 6mm | Statuario White Lux, Arabesque Pearl Lux, Breach Grey Lux, Marquina Black Lux     | NPD       | NPD                |
| ZERO.3 Eternity 6mm | Statuario White Soft, Arabesque Pearl Soft, Breach Grey Soft, Marquina Black Soft | NPD       | NPD                |